

Type	Model	UEVC1L-3210	UEVC1L-4810	UEST1L-3210	UEST1L-4810
Picture	Ref. Photo				
Price	FOB QINGDAO PORT (USD)	\$243.00	\$253.00	\$243.00	\$253.00
Input	Power Supply	L1+L2+PE	L1+L2+PE	L1+L2+PE	L1+L2+PE
	Rated Vptage	AC208~240V	AC208~240V	AC208~240V	AC208~240V
	Rated current	32A(32A, 24A, 16A,13A	48A(40A, 32A, 24A, 16A,	32A(32A, 24A, 16A,13A	48A(40A, 32A, 24A, 16A,
Output	Output Voltage	AC208~240V	AC208~240V	AC208~240V	AC208~240V
	Maximum Current	32A(32A, 24A, 16A,13A	48A(40A, 32A, 24A, 16A,	32A(32A, 24A, 16A,13A	48A(40A, 32A, 24A, 16A,
	Rated Power	7.7KW(MAX)	11.5KW(MAX)	7.7KW(MAX)	11.5KW(MAX)
Configuration	Input cable	Cable +plug	Cable +plug	Cable +plug	Cable +plug
	cable length	1M	1M	1M	1M
	Charger connector	Cable +Type1 plug	Cable +Type1 plug	Cable +Type1 plug	Cable +Type1 plug
	Cable length	5M	5M	5M	5M
	Material	ABS +PC	ABS +PC	ABS +PC	ABS +PC
	Colour	white + black	white + black	BLACK	BLACK
	Three clour led	•	•	•	•
	LCD	Optional	Optional	Optional	Optional
	Start Mode				
	Plug in and charge	•	•	•	•
	OCPP1.6J	•	•	•	•
	Tuya App	•	•	•	•
Safety	Card start	Optional	Optional	Optional	Optional
	Ingress Protection	Outshell IP65 / Connector IP54	Outshell IP65 / Connector IP54	Outshell IP65 / Connector IP54	Outshell IP65 / Connector IP54
	Impact Protection	/	/	/	/
	Over current protection	•	•	•	•
	Residual current protection (AC20mA)	•	•	•	•
	Ground protection	•	•	•	•
	Surge protection	•	•	•	•
	Over/Under voltage protection	•	•	•	•
	Over temperature	•	•	•	•
	Certification	SGS	SGS	SGS	SGS
Enviroment	Certification Standard	UL2594+UL2231+C22.2+FCC	UL2594+UL2231+C22.2+FCC	UL2594+UL2231+C22.2+FCC	UL2594+UL2231+C22.2+FCC
	Installation	Wall mounted	Wall mounted	Wall mounted	Wall mounted
	Work Temperature	‘-35℃~50℃	‘-35℃~50℃	‘-35℃~50℃	‘-35℃~50℃
	Work Humidity	3%~95%	3%~95%	3%~95%	3%~95%
	Work Altitude	<2000m	<2000m	<2000m	<2000m
Package	Procdution	330*200*105	330*200*105	320*193*105	320*193*105
	Package Dimension(L*W*H)mm	485*375*155	485*375*155	460*365*155	460*365*155
	Net weight (kg)		6.84		6.84
	Gross weight (kg)		7.84		7.84
	External container loading capacity	/	/	4 units in 1 box	4 units in 1 box
	External Package dimension mm	/	/	724*382*330mm	724*382*330mm
	Container quantity	20':1100 ;40':2220; H40':2533	20':1100 ;40':2220; H40':2533	20':1344 ;40':2688; H40':3072	20':1344 ;40':2688; H40':3072

